

ALL-IN-ONE SYSTEMS

- > Compact and flexible configuration
- > Convenient for mobile applications with built-in display
- > Powerful PC inside for fast online displays and analysis



	DEWE3-A4	DEWE3-A4L	DEWE2-A13
Slots for TRION / TRION3 modules	4 TRION / TRION3	4 TRION / TRION3	13 TRION
High-speed channel expansion	Add TRIONet3 or OXYGEN-NET		
Low-speed channel expansion	XR modules		
Data storage	1 TB SSD dedicated for data storage 512 GB SSD for operating system and application software		1 TB SSD dedicated for data storage 256 GB SSD for operating system and application software
Optional data storage	Up to 2 TB SSD		
Gapless storing rate	Typ. 400 MB/s	Typ. 400 MB/s	Typ. 90 MB/s
Display	13" TFT multi-touch, Full HD	15.4" multi-touch wide-screen display, Full HD	17" wide-screen display, Full HD
POWER SUPPLY			
Input voltage (max.)	10 to 36 V _{DC} isolated incl. external AC power supply	90 to 264 V _{AC}	90 to 264 V _{AC}
Option 1	Internal buffer battery for ~5 min operation	-	DC power supply (DW2-PS-DC-300) 10 to 36 V _{DC}
Option 2	[DW2-UPS-250-DC] External battery pack, 3 battery slots for ~2 h operation	-	[DW2-PS-BAT] Battery powered, 4 battery slots for ~2 h operation
DIMENSIONS			
Dimensions (W x D x H) without handle/feet	318 x 253 x 128 mm (12.5 x 10 x 5 in.)	462 x 320 x 135 mm (18.2 x 12.6 x 5.3 in.)	450 x 246 x 303 mm (17.7 x 9.7 x 11.9 in.)
Weight without modules and batteries ¹⁾	Typ. 5.9 kg (13 lb.)	Typ. 8.5 kg (18.7 lb.)	Typ. 15 kg (33 lb.)

¹⁾Weight of one battery: 540 g (1.20 lb.)

OPTIONS AND ACCESSORIES



External battery pack: 250 W UPS with 3 battery slots
[DW2-UPS-250-DC]



Connection box to power eight current transducers
[DW2-CLAMP-DC-POWER-8]



Industrial USB 3.0 cameras for video input
[CAM-ALVIUM-x]